

# Design and Test of Beam Diagnostics Equipment for the FAIR Proton Linac

**GSI**

**PROACTIVE R&D**

T. Sieber, P. Forck, C. Kleffner, S. Udrea - GSI Helmholtz-Zentrum für Schwerionenforschung, Darmstadt, Germany

J. Herranz - PROACTIVE R&D, Sabadell, Spain

I. Bustinduy, A. Rodriguez Paramo - ESS Bilbao, Zamudio, Spain

A. Navarro Fernandez - CERN, Geneva, Switzerland



**LINAC 2022**


**TUPOJ006**

## Abstract

A dedicated proton injector Linac (pLinac) for the Facility of Antiproton and Ion Research (FAIR) at GSI, Darmstadt, is currently under construction. It will provide a 68 MeV, up to 70 mA proton beam at a duty cycle of max. 35µs / 4 Hz for the SIS18/SIS100 synchrotrons, using the existing UNILAC transfer beamline. After further acceleration in SIS100, the protons will mainly be used for antiproton production at the Pbar ANnihilations at DArmsstadt (PANDA) experiment. The Linac will operate at 325 MHz and consists of a novel so called "Ladder" RFQ type, followed by a chain of CH-cavities, partially coupled by rf-coupling cells.

We present the beam diagnostics system for the pLinac with special emphasis on the Secondary Electron Emission (SEM) Grids and the Beam Position Monitor (BPM) system. We also describe design and status of our diagnostics testbench for stepwise Linac commissioning, which includes an energy spectrometer with associated optical system. The SEM grids and BPMs have been tested with proton and argon beams during several beamtimes in 2022. The results of these experiments are presented.

## FAIR Proton Linac Diagnostics



Parameter	Device	#	Nondestr.	Remarks
Current	Transformer	9	Yes	Dynamic Trans-mission Control
	Faraday Cup	3	No	Mainly as Beam Dumps
Profile	SEM Grids	4	No	Standard
Transv. Emit-tance & Halo Scraping	Slit Grid	3	No	Standard
Position & Mean Energy	Button BPMs	1	Yes	Position, TOF & Relative Current
		4		
Bunch Shape	New BSM / Feschenko	1	Yes / No	Under Development
LEBT: Charge state	Wien Filter	1	No	Standard (CEA)
LEBT: Emittance	Allison Scanner	1	No	Standard (CEA)

## The proton Linac:

- Serves as an injector for the FAIR synchrotrons
- High pulse current during 30 µs multi-turn injection
- Effective acceleration by CH type cavities
- Novel acc. structures ("Ladder" RFQ, CH)
- Sensitive longitudinal beam dynamics
- ⇒ **High demands for beam diagnostics**


## Basic Linac parameters

Beam energy	68 MeV
Beam current (op.)	35 mA
Beam current (des.)	70 mA
Beam pulse length	36 µs
Repetition rate	4 Hz
Rf-frequency	325.224 MHz
Tot. hor. emit. (norm.)	2.1 / 4.2 µm
Tot. mom. spread	≤ ± 10 <sup>-3</sup>
Linac length	≈ 35 m


## SEM Grid Design

### SEM Grids designed by PROACTIVE:


- Design based on PCB in combination with mech. stretching system
- 0.1 mm wires, 0.5 mm wire pitch
- detector area 32 x 32 mm
- used for beam alignment/operation and emittance measurement (grids and harps)




## Harp Simulations




## FAIR @ GSI




## BPM Test Measurements



## SEM Grid Acceptance Tests





## BPM Mechanical Design




## Test Bench and Spectrometer Design

- Test Bench used for the stepwise commissioning of the pLinac
- Includes all types of beam instrumentation devices to be used with the pLinac after the RFQ (i.e.  $E_k \geq 3$  MeV)
- Will be equipped with beam optics (quadrupoles, steerers) and a dipole for energy spread measurements




- Effect of space charge on the ion energy distribution calculated
- Investigation of energy distribution dependence on position
- pLinac MEBT triplet used for beam transport
- Spectrometer operation requires additional quadrupoles

pLinac RFQ rebuncher / MEBT section, with compact triplet lens to catch divergent beam from RFQ → beam transport similar to Test Bench



## Simulations



## BPM Electronics System LSPH

